



STAYCOLD SD1140


*High Performance
Double Sliding Door
Upright Cooler*

GREENSENSE FEATURES SAVING ENERGY AND REDUCING LIFETIME COSTS



Digital Thermostat

For accurate temperature control and built in voltage protection.



LED Lighting

Illuminating the interior of the unit for maximum visibility.



EcoMate Foam

Water based insulation foam that is non-flammable and has zero ODP.



Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.



Trust the Experience



STAYCOLD SD1140

DOUBLE DOOR COOLER

CABINET FEATURES

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Reliable, self-closing sliding doors
- Non-flammable, water based polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors



Specifications	
Climate Class	5
Nett Capacity (ltr)	746
Shelves	8
Cooling Type	Forced air
Voltage/Hz	220/50
Refrigerant	R134a
330ml Can Cap	980
330ml Bottle Cap	640

External Dimensions	
Height mm	2020
Width mm	1140
Depth mm	635

Internal Dimensions	
Height mm	1380
Width mm	1050
Depth mm	515

Packed Dimensions	
Height mm	2120
Width mm	1150
Depth mm	645
Weight kg	180

Container Loading	
20'	18
40'	36

Code	Model	Description
2070	SD1140	Std model with black trim and white Chromadek
2073	SD1140-LFS	S/S sides, hydrocarbon (R290) gas and grey trim

In the interests of continuous product development, specifications may be changed without notice.

 Unit 28, Kya Sands Industrial Village
22 Elsecar Street, Kya Sands, 2169
Randburg, South Africa

 (086) 111 3804 or
(011) 708 7548 / 0502

 stedon@maxicoolsa.co.za

 www.maxicoolsa.co.za

 @maxicoolrefrigeration

 @maxicoolrefrigeration

 Maxi Cool SA Refrigeration

