

## STAYCOLD HD580

High Performance Half Door/Impulse Cooler

## GREENSENSE FEATURES SAVING ENERGY AND REDUCING LIFETIME COSTS





For accurate temperature control and built in voltage protection.



LED Lighting

Illuminating the interior of the unit for maximum visibility.



Water based blowing agent that is non-flammable and has zero ODP.

EcoMate

Foam



Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.





## **STAYCOLD HD580**HALF DOOR / IMPULSE COOLER

## **CABINET FEATURES**

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Self-closing hinged doors
- Non-flammable, water based polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors







Specifications		
Climate Class	5	
Nett Capacity (ltr)	226	
Shelves	3	
Cooling Type	Forced air	
Voltage/Hz	220/50	
Refrigerant	R134a	
330ml Can Cap	294	
330ml Bottle Cap	168	

External Dimensions		
Height mm	1350	
Width mm	580	
Depth mm	635	

Internal Dimensions		
Height mm	840	
Width mm	490	
Depth mm	550	

Packed Dimensions		
Height mm	1450	
Width mm	590	
Depth mm	645	
Weight kg	90	

Container Loading		
20′	27	
40'	60	

Code	Model	Description
2340	HD580	Std model with black trim and white Chromadek
2343	HD580-S	Stainless steel sides and top with grey trim















